



/medias/en!hp.ec.br.pr//medias/en!hp.pv/94.173.57.19SL045007-D-PPSL0450..-PPZylinderrollenla

Cylindrical roller bearings

SL045007-D-PP (Series SL0450..-PP)

locating bearing, double row, full complement cylindrical roller set, dimension series 50, lip seals on both sides

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	35 mm
D	62 mm
B	36 mm
	30 ° Chamfer angle
C	35 mm
C ₁	30,2 mm Tolerance: +0,2/0
Ca ₁	27 mm Mounting dimension for snap ring WRE (not included in delivery) Tolerance: 0/-0,2
Ca ₂	26 mm Mounting dimension for retaining ring to DIN 471 (not included in delivery) Tolerance: 0/-0,2
D ₁	60 mm Tolerance: +0,2/0
d ₁	46,5 mm
d ₂	50 mm
d ₃	67 mm Outside diameter of snap ring WRE
d _a min	46,5 mm
m	2,1 mm
r _a max	0,3 mm
r _{min}	0,3 mm
t	0,5 mm
X	27,5 mm Distance between rolling elements

m	0,48 kg	Mass
Cr	63000 N	Basic dynamic load rating, radial
Cor	88000 N	Basic static load rating, radial
Cur	12400 N	Fatigue limit load, radial
nG	3550 1/min	Limiting speed for grease lubrication
Fett		
	WRE62	Designation for snap ring WRE (not included in delivery)
	62X2	Designation for retaining ring to DIN 471 (not included in delivery)



